

# TRANSFER-PRO™

*Moving Ahead  
With Technology*

## Precision Heat-Transfer Unit with Digital Controls



Model HT-314D/HT-315D

Model HT-310D/HT-311D

Model HT-312D/HT-313D

## ADVANTAGES

- Digital controls for precise time and temperature settings
- Adjustable pressure to accommodate various substrate thicknesses and transfer types
- Aluminum heat platen and base for faster heating and uniform temperature and pressure
- Operating temperature range up to 570° F (300° C)
- Rugged heat-tolerant silica gel mat retains shape even at maximum temperatures
- Suitable for broad range of substrates including textiles, ceramic tile, PVC and metal plates
- Compatible with standard platisol, hot-peal and sublimation transfers

A.W.T.'s Transfer-Pro™ is an easy-to-use heat transfer machine that produces quality results on a wide range of substrates with varying thicknesses, including textiles, ceramic tiles and metal plates. The Transfer-Pro line also includes a unit for applying transfers to caps. Digital controls and readouts ensure uniform output every time.

The Transfer-Pro is built to last with an all-steel housing, an aluminum heat platen and base and a silica gel pad designed to withstand the extremely high heat of transfer operations.

The Transfer-Pro comes in two sizes for flat substrates: the standard 15 x 15" (38 x 38 cm) and an oversize 16 x 24" (40 x 60 cm) platen. The cap unit features a 3 x 6.5" (8 x 17 cm) platen.



Manufactured by

**A.W.T. World Trade, Inc.**  
A Division of The A.W.T. World Trade Group

4321 N. Knox Avenue • Chicago, IL 60641 USA

773.777.7100 • Fax: 773.777.0909

sales@awt-gpi.com • www.awt-gpi.com

# Transfer-Pro™ Heat Transfer Unit

## Digital Controls for Precision Operation

### Standard Features

- Simple push-button entry of time and temperature settings with digital controls and readouts
- Temperature selectable up to 570° F (300° C)
- Timing range from 10 seconds to 6 minutes
- Easy pressure adjustment
- Audible alarm when transfer time is achieved
- Unit maintains steady heat level once preset level is attained
- One-hand operation
- Heat-tolerant silica gel pad maintains its shape and flexibility for long life
- One year warranty on heat platen
- UL-listed components



### Specifications

Cat. No	Platen Size	Electrical	Amps	Weight
<b>Transfer-Pro for T-shirts (or other flat substrate)</b>				
HT-312D	15" x 15" ( 38 x 38 cm )	110 V, 1 Ph, 60 Hz	15	55 lbs ( 25 kg )
HT-313D	15" x 15" ( 38 x 38 cm )	220 V, 1 Ph, 50 Hz	7.5	55 lbs ( 25 kg )
HT-314D	16" x 24" ( 40 x 60 cm )	110 V, 1 Ph, 60 Hz	15	88 lbs ( 40 kg )
HT-315D	16" x 24" ( 40 x 60 cm )	220 V, 1 Ph, 50 Hz	7.5	88 lbs ( 40 kg )
HT-318D (Automatic)	16" x 24" ( 40 x 60 cm )	110 V, 1 Ph, 60 Hz	15	88 lbs ( 40 kg )
HT-319D (Automatic)	16" x 24" ( 40 x 60 cm )	220 V, 1 Ph, 50 Hz	7.5	88 lbs ( 40 kg )
<b>Transfer-Pro for caps:</b>				
HT-310D	4" x 6-1/2" ( 10.15 x 16.5 cm )	110 V, 1 Ph, 60 Hz	5	31 lbs
HT-311D	4" x 6-1/2" ( 10.15 x 16.5 cm )	220 V, 1 Ph, 50 Hz	2.5	31 lbs

## The A.W.T. World Trade Group



A.W.T. World Trade Inc.

sales@awt-gpi.com  
www.awt-gpi.com



American M&M

info@screenprintmachinery.com  
www.screenprintmachinery.com



GRAPHIC PARTS INTERNATIONAL INC.

parts@gpiparts.com  
www.gpiparts.com

**For an A.W.T. dealer near you, contact:**



*Your Complete Manufacturing Source for  
Screen Printing Equipment, Supplies and Parts*



**A.W.T. World Trade, Inc.**  
A Division of The A.W.T. World Trade Group

4321 N. Knox Avenue • Chicago, IL 60641 USA

773.777.7100 • Fax: 773.777.0909

sales@awt-gpi.com • www.awt-gpi.com